

MOL-PROTEX PUN

Product Description:

MOL-PROTEX PUN is a low viscosity excellent performance metal forming lubricant intended for use in pressing, and stamping applications of stainless steel and steel alloys of high resistance. It is composed of unique blend of synthetic esters and special EP (extreme pressure) additives. It also provides corrosion protection upon application.

Properties:

- Provide outstanding load carrying properties.
- Prevent the scratching, bending and cracking.
- Has excellent oxidative and thermal stability.
- Very good anti-corrosion properties.
- Contributes to perfect surface quality.

Applications:

- Specially developed for the stamping and drawing of stainless steel and washing machine parts.
- Applied by spraying or immersion methods.
- Easily removed with alkaline or solvent type of cleaners.

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 2 years

Packing Available in:

- 20 Lit - 208 Lit

Physical and Chemical Conditions:

MOL-PROTEX PUN	Value
Appearance	Brown, Clear
Density @ 15°C, g/cm ³ ASTM D 1298	> 0.860
Flash Point (COC), °C ASTM D 92 min	> 100
Kinematic Viscosity @ 40°C, cSt	7.5
Corrosion Test	>20
Copper Corrosion @ 3 hours & 100°C	4b

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.