

4T SUPER

Product Description:

MOLLUBE 4T SUPER is a multi-grade engine oils formulated with premium mineral base oils and modern additives to provide outstanding protection in diesel and gasoline engines against wear, corrosion and oxidation.

Features:

- Keep the engine clean by eliminating the formation of sediment and preventing residue.
- Protect the engine during start-stop driving, also when the engine is cold.
- Maintain its lubrication even under extreme operating conditions.
- Reduce the chemical effects of the acid residues in the combustion chamber by formation of film layer on the metallic surfaces
- Improve the engine overhaul periods.

Applications:

MOLLUBE 4T SUPER is used in both gasoline and diesel engines. 4T super is specifically designed for use in naturally aspirated & turbocharged engines operating under severe and off highway conditions. 4T super is used in lighter duty conditions

Specifications:

- API SL/CF

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 3 years

Packing Available in:

- 1 lit - 20 lit
- 208 lit

Physical and Chemical Conditions:

MOLLUBE 4T SUPER	Method	Unit	20W-50
Density @ 15° C	ASTM D 4052	g/cm ³	0.885
Kinematic Viscosity @ 40° C	ASTM D 445	cSt	153.2
Kinematic Viscosity @ 100° C	ASTM D 445	cSt	14.4
Viscosity Index	ASTM D 2270	-	105
Flash Point, (COC)	ASTM D 92	°C	232
Pour Point	ASTM D 97	°C	-27

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.