

DYNAMIC X7 SERIES

Product Description:

MOLLUBE DYNAMIC X7 SERIES is a fully synthetic diesel heavy-duty oil produced with synthetic technology to be used in vehicles using low or high sulfur content diesel fuel.

Features:

- Protect the engine against the wear at high speeds and temperatures.
- Provide perfect protection and fuel economy under cold start-up conditions.
- Promote the combustion efficiency and maximum power output.
- Extend oil drain intervals.

Applications:

MOLLUBE DYNAMIC X7 SERIES is recommended for turbocharged and low emission diesel engines such as trucks, buses, construction machines and generators.

Specifications:

- API CI-4
- ACEA E7-08, A3/B4-08
- MB 228.3
- MAN 3275
- MTU TYPE 2
- VOLVO VDS3
- DEUTZ DQC-III

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 3 years

Packing Available in:

- 1 lit - 20 lit
- 5 lit - 208 lit

Physical and Chemical Conditions:

MOLLUBE DYNAMIC X7	Method	Unit	5W-40	10W-40
Density @ 15° C	ASTM D 4052	g/cm ³	0.87	0.885
Kinematic Viscosity @ 40° C	ASTM D 445	cSt	102	114.3
Kinematic Viscosity @ 100° C	ASTM D 445	cSt	15.01	15.9
Viscosity Index	ASTM D 2270	-	153	140
Flash Point, (COC)	ASTM D 92	°C	226	235
Pour Point	ASTM D 97	°C	-45	-25

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.