

PLATINIUM HDX 50

Product Description:

MOLLUBE PLATINIUM HDX 50 is a mono grade oil formulated from specially refined paraffinic base oil. Combined with the most modern friction modifier, detergent-dispersant, anti-corrosion, anti-wear and other protective properties.

Features:

- Outstanding oxidation and thermal stability.
- High fluidly at low temperature and excellent cold start up.
- Prolongs engine life and improve running efficiency.
- Protects engine against corrosion and wear due to special additives it contain.
- Provides engine to function properly thanks to its high viscosity index.

Applications:

MOLLUBE PLATINIUM HDX 50 is suitable to use in 4-strook natural aspirated gasoline engine, turbocharged and supercharged engines.

Specifications:

- API SF/CD

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 3 years

Packing Available in:

- 1 lit - 20 lit
- 5 lit - 208 lit

Physical and Chemical Conditions:

MOLLUBE PLATINIUM HDX 50	Method	Unit	50
Density @ 15° C	ASTM D 4052	g/cm ³	0.89
Kinematic Viscosity @ 40° C	ASTM D 445	cSt	174
Kinematic Viscosity @ 100° C	ASTM D 445	cSt	20
Viscosity Index	ASTM D 2270	-	98
Flash Point, (COC)	ASTM D 92	°C	240
Pour Point	ASTM D 97	°C	-28

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.