

PLATINIUM MEGA SERIES

Product Description:

MOLLUBE PLATINIUM MEGA SERIES is a semi synthetic based engine oil which is formulated with unique combination of high quality base oils and advanced additive technology to meet the latest requirements of gasoline engines.

Features:

- Extends engine life by providing advanced piston rod bearing wear protection.
- Advanced high and low temperature properties protect engine parts in all conditions.
- Outstanding engine cleanliness by prevents and reduces deposits and corrosion protection.
- Excellent thermal and oxidation stability and dependable rust and corrosion protection.
- Provides engine to function properly thanks to its high viscosity index.

Applications:

MOLLUBE PLATINIUM MEGA SERIES is suitable to use in 4-strook natural aspirated gasoline engine, turbocharged and supercharged engines.

Specifications:

- API SM/CF
- ACEA A3/B3,B4
- MB 229.1
- VW 500.00/505.00

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 3 years

Packing Available in:

- 1 lit
- 5 lit
- 20 lit
- 208 lit

Physical and Chemical Conditions:

MOLLUBE PLATINIUM MEGA	Method	Unit	10W-30	10W-40
Density @ 15° C	ASTM D 4052	g/cm ³	0.874	0.874
Kinematic Viscosity @ 40° C	ASTM D 445	cSt	81.7	91.2
Kinematic Viscosity @ 100° C	ASTM D 445	cSt	11.9	13.8
Viscosity Index	ASTM D 2270	-	140	154
Flash Point, (COC)	ASTM D 92	°C	225	228
Pour Point	ASTM D 97	°C	-30	-33

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.