

PLATINIUM ULTRA SERIES

Product Description:

MOLLUBE PLATINIUM ULTRA SERIES is a fully synthetic motor oil developed to meet safe driving and long usage requirements of new and modern technology gasoline engines under extreme operating conditions.

Features:

- Improved anti friction characteristics provides extreme fuel economy.
- Provide excellent wear protection in new generation and high performance gasoline vehicles.
- Superior thermal and oxidation stability maintains the performance during the long oil drain intervals.
- Excellent thermal and oxidation stability and dependable rust and corrosion protection.
- Low volatility reduce oil consumption.

Applications:

MOLLUBE PLATINIUM ULTRA SERIES is suitable to use in gasoline engine of passenger and light commercial vehicles include, catalytic convertor and turbocharger engines

Specifications:

- API SN
- ACEA A3/B3,B4
- MB 229.1
- VW 500.00/505.00
- RN 710

Health, Safety and Environment:

- Normal safety precautions (gloves and safety goggles) Should be employed
- Avoid eye and prolonged skin contact.
- Wash thoroughly after handling material.
- Don't discharge used oil in drains, dispose to an authorized used oil collection point
- For more information, please see the Material Safety Data Sheet (MSDS).

Storage Conditions:

- Should be stored sealed under normal conditions.
- Shelf life in original package and at room temperature is 3 years

Packing Available in:

- 1 lit
- 5 lit
- 20 lit
- 208 lit

Physical and Chemical Conditions:

MOLLUBE PLATINIUM ULTRA	Method	Unit	5W-30	0W-30	5W-40	0W-40
Density @ 15° C	ASTM D 4052	g/cm ³	0.859	0.864	0.862	0.845
Kinematic Viscosity @ 40° C	ASTM D 445	cSt	72.8	65	90	70.8
Kinematic Viscosity @ 100° C	ASTM D 445	cSt	12.1	12	15	12.9
Viscosity Index	ASTM D 2270	-	164	180	175	186
Flash Point, (COC)	ASTM D 92	°C	232	232	232	228
Pour Point	ASTM D 97	°C	-38	-35	-35	-35

*Meets the requirements of the OEM manufacturer.

*The stated values can fluctuate within the normal range.